



## ACEROS INOXIDABLES

LYNCH 3419 - (1437 HOA) - CAPITAL FEDERAL  
 ventas@suminox.com.ar

TEL/FAX 011-4911-8458 (L. ROTATIVAS)

### PESO POR METRO TUBOS DIAMETRO NOMINAL

Ø	Sch	Diam	Espesor	Kgs x M	Ø	Sch	Diam	Espesor	Kgs x m
1/2"	sch 5S	21,34	1,65	0,808	4"	sch 5S	114,3	2,11	5,890
1/2"	sch 10S	21,34	2,11	1,010	4"	sch 10S	114,3	3,05	8,443
1/2"	sch 40S	21,34	2,77	1,280	4"	sch 40S	114,3	6,02	16,219
1/2"	sch 80S	21,34	3,73	1,634	4"	sch 80S	114,3	8,56	22,521
3/4"	sch 5S	26,67	1,65	1,027	5"	sch 5S	141,3	2,77	9,548
3/4"	sch 10S	26,67	2,11	1,289	5"	sch 10S	141,3	3,40	11,666
3/4"	sch 40S	26,67	2,77	1,647	5"	sch 40S	141,3	6,55	21,961
3/4"	sch 80S	26,67	3,91	2,214	5"	sch 80S	141,3	9,53	31,245
1"	sch 5S	33,4	1,65	1,303	6"	sch 5S	168,28	2,77	11,407
1"	sch 10S	33,4	2,77	2,111	6"	sch 10S	168,28	3,40	13,948
1"	sch 40S	33,4	3,38	2,525	6"	sch 40S	168,28	7,11	28,512
1"	sch 80S	33,4	4,55	3,266	6"	sch 80S	168,28	10,97	42,938
1 1/4"	sch 5S	42,16	1,65	1,663	8"	sch 5S	219,08	2,77	14,908
1 1/4"	sch 10S	42,16	2,77	2,715	8"	sch 10S	219,08	3,76	20,144
1 1/4"	sch 40S	42,16	3,56	3,419	8"	sch 40S	219,08	8,18	42,925
1 1/4"	sch 80S	42,16	4,85	4,502	8"	sch 80S	219,08	12,70	65,215
1 1/2"	sch 5S	48,26	1,65	1,914	10"	sch 5S	273,05	3,40	22,812
1 1/2"	sch 10S	48,26	2,77	3,135	10"	sch 10S	273,05	4,19	28,030
1 1/2"	sch 40S	48,26	3,68	4,082	10"	sch 40S	273,05	9,27	60,841
1 1/2"	sch 80S	48,26	5,08	5,458	10"	sch 80S	273,05	12,70	82,269
2"	sch 5S	60,32	1,65	2,409	12"	sch 5S	323,85	3,96	31,519
2"	sch 10S	60,32	2,77	3,966	12"	sch 10S	323,85	4,57	36,305
2"	sch 40S	60,32	3,91	5,488	12"	sch 40S	323,85	9,53	74,532
2"	sch 80S	60,32	5,54	7,551	12"	sch 80S	323,85	12,70	98,322
2 1/2"	sch 5S	73,03	2,11	3,723	14"	sch 5S	355,6	3,96	34,647
2 1/2"	sch 10S	73,03	3,05	5,311	14"	sch 10S	355,6	4,78	41,724
2 1/2"	sch 40S	73,03	5,16	8,714	14"	sch 40S	355,6	9,53	82,060
2 1/2"	sch 80S	73,03	7,01	11,515	14"	sch 80S	355,6	12,70	108,355
3"	sch 5S	88,9	2,11	4,556	16"	sch 5S	406,4	4,19	41,932
3"	sch 10S	88,9	3,05	6,515	16"	sch 10S	406,4	4,78	47,766
3"	sch 40S	88,9	5,49	11,394	16"	sch 40S	406,4	9,53	94,106
3"	sch 80S	88,9	7,62	15,410	16"	sch 80S	406,4	12,70	124,407
3 1/2"	sch 5S	101,6	2,11	5,223	18"	sch 5S	457,2	4,19	47,228
3 1/2"	sch 10S	101,6	3,05	7,479	18"	sch 10S	457,2	4,78	53,808
3 1/2"	sch 40S	101,6	5,74	13,691	18"	sch 40S	457,2	9,53	106,152
3 1/2"	sch 80S	101,6	8,08	18,801	18"	sch 80S	457,2	12,70	140,460